



Quiet-Flow System Dimensions - TRIPLEX 3" Manifold Maximum 200 GPM

Pump Model	Motor HP	Header Size	Isolation Valves		Motor Dia.	A	B	C	D
			IN	OUT					
25S05-3	0.5	3	2.5	1.5	4	48	26	42	47.86
25S07-5	0.75	3	2.5	1.5	4	48	26	42	50.59
25S10-7	1	3	2.5	1.5	4	48	26	42	53.38
25S15-9	1.5	3	2.5	1.5	4	48	26	42	54.98
25S20-11	2	3	2.5	1.5	4	48	26	42	58.55
25S30-15	3	3	2.5	1.5	4	48	26	42	64.29
25S50-26	5	3	2.5	1.5	4	48	26	42	79.55
25S75-39 (4")	7.5	3	2.5	1.5	4	48	26	42	94.55
25S75-39DS	7.5	3	2.5	1.5	6	48	26	42	96.55
25S100-52DS	10	3	2.5	1.5	6	48	26	42	120.65
40S10-3	1	3	2.5	2	4	48	26	42	54.28
40S15-5	1.5	3	2.5	2	4	48	26	42	57.58
40S20-7	2	3	2.5	2	4	48	26	42	62.75
40S30-9	3	3	2.5	2	4	48	26	42	68.49
40S50-12	5	3	2.5	2	4	48	26	42	79.65
40S50-15	5	3	2.5	2	4	48	26	42	84.55
40S75-21	7.5	3	2.5	2	4	48	26	42	98.95
40S75-25	7.5	3	2.5	2	4	48	26	42	105.55
40S100-30	10	3	2.5	2	4	48	26	42	113.75
40S100-30 (6")	10	3	2.5	2	6	48	26	42	114.95
40S150-37DS	15	3	2.5	2	6	48	26	42	126.65
40S150-44DS	15	3	2.5	2	6	48	26	42	140.75
40S200-50DS	20	3	2.5	2	6	48	26	42	163.15
40S200-58DS	20	3	2.5	2	6	48	26	42	178.95
40S200-66DS	20	3	2.5	2	6	48	26	42	192.15
60S20-4	2	3	2.5	2	4	48	26	42	60.85
60S30-5	3	3	2.5	2	4	48	26	42	65.89
60S50-7	5	3	2.5	2	4	48	26	42	77.15
60S50-9	5	3	2.5	2	4	48	26	42	82.25
60S75-13	7.5	3	2.5	2	4	48	26	42	94.45
60S75-13 (6")	7.5	3	2.5	2	6	48	26	42	94.45
60S100-18	10	3	2.5	2	4	48	26	42	108.55
60S100-18 (6")	10	3	2.5	2	6	48	26	42	108.55
75S20-3	2	3	2.5	2	4	48	26	42	58.25
75S30-5	3	3	2.5	2	4	48	26	42	65.89
75S50-8	5	3	2.5	2	4	48	26	42	79.75
75S75-11	7.5	3	2.5	2	6	48	26	42	89.35
75S75-12	7.5	3	2.5	2	4	48	26	42	91.85
75S100-15	10	3	2.5	2	6	48	26	42	100.85
75S100-16	10	3	2.5	2	4	48	26	42	103.35
85S15-1	1.5	3	2.5	3	4	48	26	42	53.78
85S30-2	3	3	2.5	3	4	48	26	42	60.49
85S50-3	5	3	2.5	3	4	48	26	42	69.05
85S50-4	5	3	2.5	3	4	48	26	42	71.45
85S75-5	7.5	3	2.5	3	4	48	26	42	75.85
85S75-5 (6")	7.5	3	2.5	3	6	48	26	42	76.45
85S75-6	7.5	3	2.5	3	4	48	26	42	78.25
85S75-6 (6")	7.5	3	2.5	3	6	48	26	42	78.85
85S100-7	10	3	2.5	3	4	48	26	42	81.75
85S100-7 (6")	10	3	2.5	3	6	48	26	42	82.45



**Quiet-Flow System Dimensions - TRIPLEX
3" Manifold
Maximum 200 GPM**

Pump Model	Motor HP	Header Size	Isolation Valves		Motor Dia.	A	B	C	D
			IN	OUT					
85S100-8	10	3	2.5	3	4	48	26	42	84.15
85S100-8 (6")	10	3	2.5	3	6	48	26	42	84.75
85S100-9	10	3	2.5	3	4	48	26	42	86.55
85S100-9 (6")	10	3	2.5	3	6	48	26	42	87.15
85S150-10	15	3	2.5	3	6	48	26	42	92.15
85S150-11	15	3	2.5	3	6	48	26	42	94.55
85S150-12	15	3	2.5	3	6	48	26	42	96.95
85S150-13	15	3	2.5	3	6	48	26	42	99.35
85S200-14	20	3	2.5	3	6	48	26	42	104.25
85S200-15	20	3	2.5	3	6	48	26	42	106.65
85S200-16	20	3	2.5	3	6	48	26	42	109.05
85S200-17	20	3	2.5	3	6	48	26	42	111.45
85S200-18	20	3	2.5	3	6	48	26	42	113.85
85S250-19	25	3	2.5	3	6	52	26	42	116.15
85S250-20	25	3	2.5	3	6	52	26	42	121.65
85S250-21	25	3	2.5	3	6	52	26	42	124.05
85S250-22	25	3	2.5	3	6	52	26	42	126.45
85S300-23	30	3	2.5	3	6	52	26	42	129.05
85S300-24	30	3	2.5	3	6	52	26	42	133.85
85S300-25	30	3	2.5	3	6	52	26	42	136.15
85S300-26	30	3	2.5	3	6	52	26	42	138.55
85S300-27	30	3	2.5	3	6	52	26	42	140.95
85S400-28	40	3	2.5	3	6	52	26	42	143.35
85S400-29	40	3	2.5	3	6	52	26	42	150.85
85S400-30	40	3	2.5	3	6	52	26	42	153.15
85S400-33	40	3	2.5	3	6	52	26	42	169.45
85S400-33 (8")	40	3	2.5	3	8	52	26	42	171.05
85S400-36	40	3	2.5	3	6	52	26	42	176.65
85S400-36 (8")	40	3	2.5	3	8	52	26	42	172.25
85S500-39	50	3	2.5	3	6	52	26	42	183.75
85S500-39 (8")	50	3	2.5	3	8	52	26	42	179.35
150S20-1	2	3	2.5	3	4	48	26	42	57.05
150S50-2	5	3	2.5	3	4	48	26	42	69.45
150S75-3	7.5	3	2.5	3	4	48	26	42	75.25
150S75-4	7.5	3	2.5	3	4	48	26	42	79.05
150S75-4 (6")	7.5	3	2.5	3	6	48	26	42	79.65
150S100-5	10	3	2.5	3	4	48	26	42	84.05
150S100-5 (6")	10	3	2.5	3	6	48	26	42	84.65
150S150-6	15	3	2.5	3	6	48	26	42	91.05
150S150-7	15	3	2.5	3	6	48	26	42	94.75
150S150-8	15	3	2.5	3	6	48	26	42	98.55
150S200-10	20	3	2.5	3	6	48	26	42	108.75
150S200-11	20	3	2.5	3	6	48	26	42	112.55
150S200-9	20	3	2.5	3	6	48	26	42	104.95
150S250-12	25	3	2.5	3	6	52	26	42	118.75
150S250-13	25	3	2.5	3	6	52	26	42	122.55
150S250-14	25	3	2.5	3	6	52	26	42	126.35
150S300-15	30	3	2.5	3	6	52	26	42	132.75
150S300-16	30	3	2.5	3	6	52	26	42	136.55
150S300-17	30	3	2.5	3	6	52	26	42	140.25



Quiet-Flow System Dimensions - TRIPLEX 3" Manifold Maximum 200 GPM

Pump Model	Motor HP	Header	Isolation Valves		Motor Dia.	A	B	C	D
		Size	IN	OUT					
150S400-18	40	3	2.5	3	6	52	26	42	149.15
150S400-19	40	3	2.5	3	6	52	26	42	152.95
150S400-20	40	3	2.5	3	6	52	26	42	156.75
150S400-21	40	3	2.5	3	6	52	26	42	160.55
150S400-22	40	3	2.5	3	6	52	26	42	164.25
150S400-23	40	3	2.5	3	6	52	26	42	168.05
150S500-24	50	3	2.5	3	6	52	26	42	189.45
150S500-24 (8")	50	3	2.5	3	8	52	26	42	173.55
150S500-25	50	3	2.5	3	6	52	26	42	193.25
150S500-25 (8")	50	3	2.5	3	8	52	26	42	177.35
150S500-26	50	3	2.5	3	6	52	26	42	197.05
150S500-26 (8")	50	3	2.5	3	8	52	26	42	181.15
150S500-27	50	3	2.5	3	6	52	26	42	200.85
150S500-27 (8")	50	3	2.5	3	8	52	26	42	184.95
150S500-28	50	3	2.5	3	6	52	26	42	204.65
150S500-28 (8")	50	3	2.5	3	8	52	26	42	188.75
150S600-29	60	3	2.5	3	6	52	26	42	214.95
150S600-29 (8")	60	3	2.5	3	8	52	26	42	197.05
150S600-31	60	3	2.5	3	6	52	26	42	228.55
150S600-31 (8")	60	3	2.5	3	8	52	26	42	207.65
150S600-33	60	3	2.5	3	6	52	26	42	236.05
150S600-33 (8")	60	3	2.5	3	8	52	26	42	215.15
150S750-36	75	3	2.5	3	8	52	26	42	226.55
150S750-39	75	3	2.5	3	8	52	26	42	242.85

Notes:

1. All dimensions are in inches unless specified otherwise.
2. Not for construction purposes unless certified.
3. Structural members are 2" Stainless Steel tubing unless indicated otherwise.
4. See Drawing #DVQF-VFD-LL for references to measurements